




BEFORE TOWING EASY STRIKER

1. Check turn signals, brake lights, driving lights and emergency flashers.
2. Check coupler to see if it's fastened and locked down tight on ball. NOTICE: The hitch ball must be 2 5/16" when attaching the hitch. Anything bigger or smaller will not fit.
3. Put 1/4" safety bolt through coupler.
4. Safety chains should be crossed under the tongue of the trailer and correctly fastened.
5. Make sure supporting legs are folded up and fastened against frame with chain and secured with a nut according to Government of Alberta Ministry of Transportation.

HOW TO SET UP EASY STRIKER

	CAUTION
	<ul style="list-style-type: none">• Keep the Easy Striker away from power lines.• Do not operate during storms or strong winds.• Periodically, check the bolts to make sure they are tightly fastened.• Use only on level, firm ground. Stake the unit down if necessary• Be sure to always use the support legs to avoid having the unit tip over.• Block off a "striking zone" with plenty of room for the participant to safely wing the mallet with no danger of hitting a spectator or passer-by.• Before each use, inspect mallet and make sure handle is on tight.• Only one person at a time in the striking zone.• Do not leave the unit unattended.• Do not allow anyone to climb on the Easy Striker

1. Select a level area for set up.
2. Unhook trailer and lights from tow vehicle and roll to set up area.
3. Carefully raise the unit into its upright position. NOTICE: Assistance will be required.
4. Remove the nut and unlock the safety chain from the support legs and swing them down so that they are firmly resting on the ground. Wrap the chain around the frame and lock.